

C-Series™ - Cast Iron Pumps

Belt Drive - 240V - High Pressure

Built in Australia.

**2 stage “high pressure” pump.
For applications such as truck tyre fitting, bead blasting & inflation, manufacturing and much more.**

160psi High Pressure

Perfect for truck tyres

- ◆ Rated to AS4637.
- ◆ 2 stage, up to 160psi for high pressure applications.
- ◆ Heavy duty “close grain” cast iron pump.
- ◆ Featuring highly efficient reed valves.
- ◆ Fully balanced flywheel with large cooling blades.
- ◆ TECO motor with overload protection.
- ◆ Supported by TECO National Service Network.
- ◆ Capacitor start/Capacitor run.
- ◆ Filter/regulator included.
- ◆ 2 x regulated outlets.
- ◆ 1 x unregulated high pressure tank outlet.
- ◆ Guarding meets Occupational Health & Safety Standards.
- ◆ Tank meets Australian Standard AS1210.
- ◆ Full range of spare parts available.
- ◆ Warranty.
 - 5 years on pump*
 - 5 years on tank*
 - 1 year on motor & fittings*
- ◆ Dual control option available for all models.**



C16-HP



C16L-HP



Dimensions (mm)	Length	Width	Height	Weight (kg)
C16-HP	1,100	480	820	98
C16L-HP	1,450	400	900	117
Petrol Model				
CP20-HP	1,100	480	900	100

* Dimensions exclude wheels and handle

Product Code	Displacement CFM	L/min	Free Air Delivery CFM	L/min	Motor Hp	Tank Litres	Power Supply	Max. Pressure	Cylinders
C16-HP	14.5	410	11.6	328	3.0	73	15A	160psi	W-Triple
C16L-HP	14.5	410	11.6	328	3.0	125	15A	160psi	W-Triple
Petrol Model									
CP20-HP	15.0	424	12.0	340	6.5	73	GX200	160psi	W-Triple

* Applies to electric models only. Warranty for petrol model CP20-HP - 3 years on pump, 3 years on Honda engine, 5 years on tank.

* Filter regulator not included on petrol models.

CFM x 28.3 = Litres per minute
Displacement & FAD calculated at 100psi.
Specifications/configuration may change at any time without notice.

Add Constant Run Option if used with bad power or a generator.